

ALESO RC

Bore gauge with manual recall of the mechanism
Alesometro con richiamo manuale del meccanismo

BORE GAUGES ALESAMETRI


- Mobile tip in MD (Widia) integral and with radius
- Interchangeable fixed tips with sphere MD (Widia)
- $\varnothing 8$ mm dial gauge clamping shank
- Dial Gauge not included
- Probe Release
- Handle with insulation chamber
- Supplied with dial gauge 0,01 $\varnothing 60$
- Aluminum protection for the dial gauge (PROTI)
- Puntale mobile MD (Widia) integrale raggiato a richiamo
- Puntali fissi intercambiabili con sfera MD (Widia)
- Attacco per comparatore $\varnothing 8$ mm
- Comparatore non fornito
- Richiamo tastatore
- Impugnatura con camera di isolamento
- Di serie comparatore 0,01 $\varnothing 60$
- Protezione in alluminio per il comparatore (PROTI)



Probe r8
Puntale r8



Manual probe release
Richiamo manuale puntale



Article	Range (mm)	Hole depth (mm)	A	B	Accuracy μm^*	Repeatability μm	Code	Kg
ALESO RC 30-100	30-100	140	165	13	± 1	1	D00210	0,160
ALESO RC 50-160	50-160	140	170	13	± 1	1	D00215	0,190
ALESO RC 100-300	100-300	220	245	15	± 1	1	D00225	0,400

*Accuracy on 0.5 mm measuring travel (excluding dial gauge)

*Precisione con escursione di 0,5 mm (escluso comparatore)